ECC)-TERR®

Slab Cut Sheet

COVERINGS



Standart



Overview

Embrace quality and style with Eco-Terr® Slabs, your optimal choice for flooring and countertops. Eco-Terr® is crafted from Future-Friendly™ material, a unique blend of recycled natural stone aggregates.

These slabs are not only aesthetically pleasing but also built to last, thanks to their durable, zero VOC materials. The cleanable finish is resistant to microbial growth and prevents moisture accumulation. Consequently, it aids in maintaining a moldfree environment and enhances indoor air quality.

Contains pre-consumer recycled content; may help contribute toward LEED® credits with USGBC project certification.

Specifications

Coeffi cient of Friction	ASTM C-1028	Dry: 0,64; Wet: 0,61
Resistance to Fire	ASTM Class 0	
Freeze-Thaw	ASTM C-666	None (300 cycles)
Compressive Strenght	ASTM C-170	8,000 - 2,000 psi
Modulus of Rupture	ASTM C-99	1,250 psi
Flexural Strength	ASTM C-880	1,572 psi
Water Absorption	ASTM C-97	5.2%

AVAILABLE SIZES

Sheets 100" x 56" x 1 1/4"

120" x 49" x 1 1/4"

FINISHES

Honed, Brushed, and Polish.

COLLECTION





